



Double electric and automatic steam generator, available with variable power

Double electric and automatic steam generator, available with variable steam production from 40 to 120 kW. Water feed can be connected directly to the water mains or to a condensate tank.

The boiler is supplied with four heaters, which can be switched on all together, in order to get the maximum power output, or individually.

Options

- Stainless steel condensate recovery tank (160 l)
- Boiler body in stainless steel AISI 304
- All components in contact with water in stainless steel AISI 304

Technical Specifications	MAXI 120
Voltage	230V/400V/3/50-60 Hz
Steam working pressure	0,3 ÷ 7 bar
Boiler capacity	2 x 55 l
Pump motor	2 x 0.55 kW
Steam tap height	530-1350 mm
Condensate recovery height	280-1120 mm
Overall dimensions	830x830x1395 mm
Net weight	237 Kg
Gross weight (crate)	281 Kg
Packing dimensions	930x930x1700 mm

Available electric powers and steam output (for each boiler vessel)		
kW	kCal/h	Kg/h
20 (10+10)	17.200	25 ÷ 27
24 (12+12)	20.600	31 ÷ 33
30 (15+15)	25.800	40 ÷ 42
30 (20+10)	25.800	40 ÷ 42
36 (18+18)	31.000	48 ÷ 50
40 (20+20)	32.700	53 ÷ 55
50 (25+25)	43.050	68 ÷ 70
60 (30+30)	51.700	81 ÷ 83

The firm reserves the right to make any necessary modification without prior notice.