



Vacuum, up-steaming and blowing table with or without boiler

Steaming, vacuum and blowing finishing table with utility board. Thanks to its versatility **VAPOR GB-S** assures high speed whilst maintaining an excellent ironing quality. The machine is available on request with pedals on both sides. That's important during the blowing operation works with the point of the board to the right. **VAPOR GB-S** has been designed for two swinging arms with suction and different interchangeable shapes.

Following versions are available:

VAPOR AS Std: with Standard-utility board 1200x400x250 mm, with built-in boiler of 16 litres-capacity and iron

VAPOR AS Maxi: with Maxi-utility board 1300x500x250 mm, with built-in boiler of 16 litres-capacity and iron;

VAPOR VS Std: with Standard-utility board 1200x400x250 mm, to be connected to external steam supply. Iron included.

VAPOR VS Maxi: with Maxi-utility board 1300x500x250 mm, to be connected to external steam supply. Iron included;

VAPOR ES Std: with built-in steam boiler of 7 litres-capacity, with standard blowing board (1200x400x250 mm)

Technical Spec.	VAPOR AS Std	VAPOR AS Maxi	VAPOR VS Std	VAPOR VS Maxi	VAPOR ES Std
Voltage	230V/400V/3/50-60Hz	230V/400V/3/50-60Hz	230V/400V/1/50-60Hz	230V/400V/1/50-60Hz	230V/400V/3/50-60Hz
Water inlet	Ø 3/8"	Ø 3/8"	--	--	Ø 3/8"
Steam inlet	--	--	3/8"	3/8"	--
Air inlet	Ø 1/4"	Ø 1/4"	Ø 1/4"	Ø 1/4"	Ø 1/4"
Steam working press.	4,5 bar	4,5 bar	--	--	4,5 bar
Air working pressure	4 ÷ 8 bar	4 ÷ 8 bar	4 ÷ 8 bar	4 ÷ 8 bar	4 ÷ 8 bar
Steam consumption	10 ÷ 15 Kg/h	10 ÷ 15 Kg/h	10 ÷ 15 Kg/h	10 ÷ 15 Kg/h	7 ÷ 10 Kg/h
Air consumption	5 NI/ min.	5 NI/ min.	5 NI/ min.	5 NI/ min.	5 NI/min.
Boiler heater	7-10-12-15 kW	7-10-12-15 kW	--	--	6 - 7.5 kW
Iron heater	0.830 kW	0.830 kW	0.830 kW	0.830 kW	0.830 kW
Suct./blowing motor	0.60 HP	0.60 HP	0.60 HP	0.60 HP	0.60 HP
Pump motor	0.75 HP	0.75 HP	--	--	0.75 HP
Suction outlet	Ø120 mm	Ø120 mm	Ø120 mm	Ø120 mm	Ø120 mm
Boiler exhaust	Ø 1/2"	Ø 1/2"	--	--	Ø 3/8" mm
Board dimensions	1200x400x250mm	1300x500x250mm	1200x400x250mm	1300x500x250mm	1200x400x250mm
Overall dimensions	1680x580x920mm	1780x580x920mm	1680x580x920mm	1780x580x920mm	1680x580x920mm
Net weight	155 Kg	168 Kg	110 Kg	123 Kg	141 kg
Gross w. (carton pallet)	179 Kg	192 Kg	134 Kg	147 Kg	165 kg
Packing dimensions	1880x680x1270mm	1880x680x1270mm	1880x680x1270mm	1880x680x1270mm	1880x680x1270mm
Volume	1.60 m ³	1.74 m ³	1.60 m ³	1.74 m ³	1.60 m ³

- | Options |
|--|
| - Swinging arm with suction and heated sleeve shape |
| - Swinging arm with suction and heated egg shape |
| - Swinging arm with suction and spotting shape |
| - Steam gun |
| - Steam-air gun |
| - Water spray gun with support or atomiser on the handle of the iron |
| - Cold spotting gun with tank. |
| - Sliding trolley with balancer with or without lighting |
| - Lighting |
| - Swinging iron-rest |
| - Pedals on both sides of the table |

The firm reserves the right to make any necessary modification without notice.