



Automatic and electric steam boiler, power between 15 and 60 kW, steam pressure from 0.5 to 7 bar

Electric and automatic steam generator, available steam production from 15 to 60 kW. Water feed can be connected directly to the water mains or to a condensate tank. MAXI 60 is supplied with two separate sets of heating elements for single or double operation.

Steam working pressure is between 0.5 to 7 bar.

Options

- Stainless steel condensate recovery and water feed tank (83 l)
- Boiler body in stainless steel AISI 304
- All components in contact with water in stainless steel AISI 304

Technical Specifications

MAXI 60

Voltage	230V/400V/3/50-60 Hz
Steam working pressure	0,3 ÷ 7 bar
Boiler capacity	55 l
Pump motor	0.55 kW
Steam tap height	510 mm
Condensate recovery	300 mm
Overall dimensions	830x830x570 mm
Net weight	114 Kg
Gross weight (carton-pallet)	131 Kg
Packing dimensions	900x900x820 mm

Available electric powers and steam output

kW	kCal/h	Kg/h
20 (10+10)	17.200	25 ÷ 27
24 (12+12)	20.600	31 ÷ 33
30 (15+15)	25.800	40 ÷ 42
30 (20+10)	25.800	40 ÷ 42
36 (18+18)	31.000	48 ÷ 50
40 (20+20)	32.700	53 ÷ 55
50 (25+25)	43.050	68 ÷ 70
60 (30+30)	51.700	81 ÷ 83

The firm reserves the right to make any necessary modification without notice.