



Cold spotting table with or without built-in suction unit and compressor

- Cold spotting table
- Board (800x260x175mm) out of stainless steel AISI 304

- Featuring two cold spotting guns with independent circuits, two receptacles for liquids, hose support and swinging arm with suction and spotting shape out of stainless steel AISI 304

| Technical Specifications | GB-S-88 F |
|-------------------------------|--------------------------|
| Voltage | 230V/ 1 / 50-60 Hz |
| Air working pressure | 4 ÷ 8 bar |
| Steam working pressure | 4,5 bar max |
| Air consumption | 200 NI/min. |
| Steam consumption | 2 ÷ 3 Kg/h |
| Suction motor | 0,6 HP |
| Compressor motor | 2,0 HP |
| Steam inlet | 3/8" |
| Return outlet | 3/8" |
| Board dimensions | 800 x 260 x 175 mm |
| Overall dimensions | 1200 x 650 x 1800 mm |
| Net weight | 44 Kg / 78 Kg (+ compr.) |
| Gross weight (carton-pallet) | 58 Kg |
| Gross weight + compr. (crate) | 145 Kg |
| Overall dim. (carton-pallet) | 1300 x 540 x 1160 mm |
| Packing dimensions (crate) | 1340 x 960 x 1170 mm |

Options

- Built-in compressor (three-phase motor)
- Built-in vacuum unit (single-phase motor)
- Pneumatic valve for central suction connection
- Steam-air gun assembly
- Lighting

The firm reserves the right to make any necessary modification without notice.